


## With beeper



- No need to rotate while measuring.
- The red light was sealed with setting red-glue; it can concentrate the light and resist water.
- The sensor beeps while the red light is on.
- The sensor will beep when the user couldn't see the reverse side or get a clear sight.
- Example. If sensor's light is working, visually you couldn't see inside of the inner hole, while probing the user can be warned by the
- When probe the deep hole, you can't see the red light, but you can hear the sound from beeper.
- Accuracy: within 0.005mm.



## **OPTICAL TYPE WITH BEEPER**

	Onitanini				
IGHT kg)	CODE NO.				
0.4	3402-001				
~ -	0.400,000				

**Optical Type** 

ORDER NO.	D	d1	d2	L	11	12	BATTERY TYPE	WEIGHT (kg)	CODE NO.
VPS-20E	Ø20	18	10	157	77	41	UM-5#(SP) x1PCS/12V	0.4	3402-001
VPS-32E	Ø32	18	10	157	74	41		0.7	3402-002

## Touch Point Sensor



Red pilot can be seen clearly. Whole travel of red pilot is sparkling, detecting also can be done during turning while spindle stops.

High sensitivity position sensor.

- Location of end surface, outter circle dia.,inner circle dia. of the workpiece for processing can be detected with full effect.
- Deviced with safety line excess, ball supported by spring, so even line excess, it will be separtated easily from the base shown as the fig.
- The precision will reach up to micrometer while the ball returns to center position.





Fig.



## OPTICAL TYPE

ORDER NO.	D	d1	d2	L	11	12	BATTERY TYPE	WEIGHT (kg)	CODE NO.
VPS-20	20	18	10	157	76	33	UM-5#(SP) x2P/R1./1.5V	0.4	3402-003
VPS-32	32	18	10	157	74	41		0.7	3402-004

