

Micrometer

Caliper Type Micrometers
SERIES 343

- Effective for measuring workpiece features where access is difficult with a standard micrometer.
- Measuring faces: Carbide tipped
- Equipped with Ratchet Stop for constant measuring force.




SPECIFICATIONS

Metric					
Code No.	Range (mm)	Resolution (mm)	Maximum permissible error J/MP (μm)	Flatness (μm)	Parallelism (μm)
With SPC data output					
343-250-30	0 - 25	0.001	±5	0.3	3
343-251-30	25 - 50		±6		
343-252-30	50 - 75		±7		
343-253-30	75 - 100		±8		4


Inch / Metric					
Code No.	Range (in)	Graduation (in)	Maximum permissible error J/MP (in)	Flatness (in)	Parallelism (in)
With SPC data output					
343-350-30	0 - 1	0.00005 in/ 0.001 mm	±0.00025	0.000012	0.00012
343-351-30	1 - 2		±0.0003		
343-352-30	2 - 3		±0.00035		
343-353-30	3 - 4		±0.0004		0.00016

- Power source: SR44 battery (1 pc.), **938882** included as standard (for operational checks)
 - Battery life: Approx. 2.4 years under normal use
 - Position detection method: Electromagnetic rotary sensor
 - Standard accessories: Setting standard, 1 pc. (except for measuring range 0 to 25 mm (0 to 1 in) models), Spanner (**301336**), 1 pc.
- Note: For functional details of **series 343**, refer to page 02-7.
Please note that these models are not water-proof.

DIMENSIONS



Measurement example



Optional Accessories (for series 343)

Code No.	Type	Description
264-020	—	USB Input Tool Series USB Keyboard Signal Conversion Type IT-020U
05CZA662	B	Connection cable (1 m)
05CZA663	B	Connection cable (2 m)
06AFM380B	B	USB Input Tool Direct (2 m)
02AZD730G	IP67	U-WAVE-T
02AZD880G	Buzzer	U-WAVE-T
02AZE200	—	U-WAVE-T mounting bracket
02AZD790B	B	Connection cable for U-WAVE-T (160 mm)
02AZE140B	B	Connection cable for U-WAVE-T For foot switch
264-622	IP67	U-WAVE-TM
264-623	Buzzer	U-WAVE-TM
264-626	IP67	U-WAVE-TMB
264-627	Buzzer	U-WAVE-TMB
02AZF310	IP67	Connecting unit for U-WAVE-TM/TMB

