Special Purpose Micrometers

Dial Snap Meters SERIES 523

- The snap meter with a built-in dial indicator enables accurate Go/No-go judgement without interruption. Pushing the retractable anvil button causes the anvil and pointer to move, enabling speedy measuremets.
- Designed for use with a stand to enable a more stable measurement.

523-121

- Greatly improved accuracy: indication accuracy and graduation of 1 µm.
- IP protection level: 54, coolant-splash resistant during grinding process.
- Hard-coated crystal: enhanced oil and scratch resistance.




SPECIFICATIONS

Metric —										
Code N	No.	Range (mm)	Dial graduation (mm)	Measuring force (N)	Flatness (µm)		Dispersion of indication (µm)			
523-12	21	0 - 25	0.001	5 - 10	0.3	0.6	0.4	1	±0.06	740
523-12	22	25 - 50				0.0				840
523-12	23	50 - 75				1				950
523-12	24	75 - 100								1080

	Inch									
	Code No.	Range (in)	Dial graduation (in)	Measuring force (N)	Flatness (in)		Dispersion of indication (in)		Indicating range (in)	Mass (g)
Ī	523-131	0 - 1	0.00005	5 - 10	0.000012	0.000024	0.00002	0.00005	±0.0023	740
	523-132	1 - 2								840
	523-133	2 - 3				0.00004				950
ĺ	523-134	3 - 4								1080

DIMENSIONS





Measurement example

